

Providing valuable products from valuable people to valuable customers™

Kold Flo® Pourable Asphalt and Concrete Crack Filler

Kold Flo is a safe, easy-to-use, modified asphalt emulsion crack filler designed for maintenance of asphalt and concrete pavements. It prevents cracks from becoming potholes by sealing them from the weather's destructive freeze and thaw cycles. Kold Flo is ideal for roads, highways, parking lots, and driveways. When properly applied, Kold Flo can be driven over within 30 minutes without tracking.

Ready to Use

Kold Flo is available in 55-gallon drums, 5-gallon pails and easy pour 1-gallon bottles. No waiting for kettles to heat up means crews are ready to go in minutes. Apply Kold Flo from the original container, with a pour pot, or a drum pump for faster application. No special equipment or training is required. Homeowners and do-it-yourselfers especially like the 1-gallon bottle with pour spout for easy use around the house.

Safe and Easy Application

Kold Flo crack filler is safe and easy to use. No heating means no burns. It's ready-to-use with no wasted material.

Kold Flo is applied in an easy three-step process

- Blow or sweep debris from cracks.
- Pour Kold Flo into the crack, 3/4 of the length. Allow a few minutes for Kold Flo to seep down into the crack.
- Using a "U" shaped squeegee, push Kold Flo into the crack allowing the excess to fill the remaining 1/4 length of the crack. If cracks are deeper than 2", a second application may be required. Use on cracks between 1/4" and 1" wide.
- Use UPM® Permanent Pavement Repair Material for larger cracks or deteriorated expansion joints.

Coverage (per gallon)

1/4" (wide) x 1/4" (deep) = 300 linear feet

1/2" (wide) x 1/2" (deep) = 75 linear feet

1" (wide) x 1" (deep) = 25 linear feet

Fast Curing

When properly applied, Kold Flo can be driven over within 30 minutes without tracking, minimizing traffic delays.

Kold Flo is applied in an easy three-step process

STEP 1

Blow or sweep debris from cracks.



STEP 2

Pour Kold Flo into the crack, 3/4 of the length. Allow a few minutes for Kold Flo to seep down into the crack.



STEP 3

Using a "U" shaped squeegee, push Kold Flo into the crack allowing the excess to fill the remaining 1/4 length of the crack. If cracks are deeper than 2", a second application may be required. Use on cracks between 1/4" and 1" wide.



Note: Use UPM® Permanent Pavement Repair Material for larger cracks or deteriorated expansion joints.

Additional Information

- KEEP FROM FREEZING! Kold Flo is an asphalt emulsion and must be stored at temperatures above 35°F.
- Kold Flo should be applied when the ambient temperature is at least 50°F with no chance of rain for 8 hours. Extraneous water will destroy Kold Flo if it has not yet cured.
- Kold Flo stored longer than three months may require stirring due to slight settling.
- Clean tools with water immediately after use. If Kold Flo is cured, use only EPA approved solvents for cleaning. If Kold Flo dries on hands, use only EPA/OSHA approved hand cleaners.

Proudly made in the USA